

MKT Metall-Kunststoff-Technik GmbH & Co. KG
67685 Weilerbach

Date printed 09.02.2015, Revision 25.03.2014

Version 03. Supersedes version: 02

Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

MKT Injektionsmörtel VMU-PLUS, Comp. A

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Adhesive mortar for fastening elements A-Component (Resin)

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

MKT Metall-Kunststoff-Technik GmbH & Co. KG
Auf dem Immel 2
67685 Weilerbach / GERMANY
Phone +49(0)6374-91 16-0
Fax +49(0)6374-91 16-60
Homepage www.mkt.de
E-mail info@mkt.de

Address enquiries to

Technical information

mkt@mkt.de

Safety Data Sheet

mkt@mkt.de

1.4 Emergency telephone number

Advisory body

+49 (0)89-19240 (24h) (english)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008 [CLP]

STOT SE 3: H335 May cause respiratory irritation.
Skin Sens. 1: H317 May cause an allergic skin reaction.

2.1.2 Classification according to Directive 67/548/EEC or 1999/45/EC

Xi, Irritant - R 37: Irritating to respiratory system.
Sensitizing. - R 43: May cause sensitisation by skin contact.

2.2 Label elements

The product is classified and required to be labelled in accordance with EC-Directives

Labelling according to Regulation (EC) 1272/2008

Hazard pictograms



Signal word

WARNING

Contains:

Ethylene dimethacrylate
Methacrylic acid, monoester with Propan-1,2-diole

Hazard statements

H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P261 Avoid breathing vapours.
P280 Wear protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P501 Dispose of contents/container to in accordance with local/regional/national/international regulation.

MKT Metall-Kunststoff-Technik GmbH & Co. KG
67685 Weilerbach

Date printed 09.02.2015, Revision 25.03.2014

Version 03. Supersedes version: 02

Page 2 / 9

2.3 Other hazards

Human health dangers	Persons already sensitised to methacrylates may develop allergic reactions when using this product.
Environmental hazards	Does not contain any PBT or vPvB substances.
Other hazards	Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
10 - <20	Ethylene dimethacrylate CAS: 97-90-5, EINECS/ELINCS: 202-617-2, EU-INDEX: 607-114-00-5 GHS/CLP: STOT SE 3: H335 - Skin Sens. 1: H317 EEC: Xi, R 37-43
1 - <10	Methacrylic acid, monoester with Propan-1,2-diole CAS: 27813-02-1, EINECS/ELINCS: 248-666-3 GHS/CLP: Eye Irrit. 2: H319 - Skin Sens. 1: H317 EEC: Xi, R 36-43
0,1 - <1	1,1'-(p-Tolylimino)dipropan-2-ol CAS: 38668-48-3, EINECS/ELINCS: 254-075-1 GHS/CLP: Acute Tox. 3: H301 - Eye Dam. 1: H318 - Aquatic Chronic 3: H412 EEC: T, R 25-41-52/53
1 - <5	Quartz (< 10µm) CAS: 14808-60-7, EINECS/ELINCS: 238-878-4 GHS/CLP: STOT RE 1: H372 EEC: Xn, R 48/20

Comment on component parts	The quartz in this preparation is not available on foreseeable use. It does not contain a component of the PRTR register (Pollutant Release and Transfer Register). All chemical substances in this material are included on or exempted from listing on the ENCS Inventory. Substances of Very High Concern - SVHC: substances are not contained or are below 0,1%. For full text of H-statements and R-phrases: see SECTION 16.
-----------------------------------	---

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Take off contaminated clothing and wash before reuse.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek for medical treatment.
Skin contact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Supply with medical care. Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects
Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

MKT Metall-Kunststoff-Technik GmbH & Co. KG
67685 Weilerbach

Date printed 09.02.2015, Revision 25.03.2014

Version 03. Supersedes version: 02

Page 3 / 9

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide.
Dry powder.
Water spray jet.

Extinguishing media that must not be used Full water jet
Foam.

5.2 Special hazards arising from the substance or mixture

In the event of fire the following can be released:
Carbon monoxide (CO)

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.
Fire residues must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Use personal protective equipment.
High risk of slipping due to leakage/spillage of product.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.
In case the product spills into drains/surface waters/groundwater, immediately inform the authorities.

6.3 Methods and material for containment and cleaning up

Take up mechanically.
Take up residues with absorbent material (e.g. sand, sawdust, generalpurpose binder, diatomaceous earth).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.

Take off contaminated clothing and wash before reuse.
Do not eat, drink, smoke or take drugs at work.
Wash hands before breaks and after work.
Use barrier skin cream.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with food and animal food/diet.
Keep container in a well-ventilated place.
Keep container tightly closed.
Keep in a cool place. Store in a dry place.
Protect from atmospheric moisture and water.
Store in a dark place.
Recommended storage temperature: 5 - 25 °C

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Range [%]	Substance
1 - <5	Quartz (< 10µm)
	CAS: 14808-60-7, EINECS/ELINCS: 238-878-4
	Long-term exposure: 0,15 mg/m ³ , HSE, NIOSH, OSHA

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation.
Eye protection	Tightly fitting goggles.
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. Nitrile rubber, >480 min (EN 374).
Skin protection	Protective clothing.
Other	Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective supplier.
Respiratory protection	If ventilation insufficient, wear respiratory protection. Short term: filter apparatus, combination filter A-P2.
Thermal hazards	not applicable
Delimitation and monitoring of the environmental exposition	Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	pasty
Color	light beige
Odor	characteristic
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	not determined
Flash point [°C]	not applicable
Flammability (solid, gas) [°C]	not determined
Lower explosion limit	not determined
Upper explosion limit	not determined
Oxidizing properties	not determined
Vapour pressure/gas pressure [kPa]	not determined
Density [g/ml]	1,52 - 1,68 (23°C / 73,4°F)
Bulk density [kg/m³]	not applicable
Solubility in water	insoluble
Partition coefficient [n-octanol/water]	not determined
Viscosity	not determined
Relative vapour density determined in air	not determined
Evaporation speed	not determined
Melting point [°C]	not determined
Autoignition temperature [°C]	not determined
Decomposition temperature [°C]	not determined

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

The product is stable under standard conditions.

10.3 Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Strong oxidizing agent.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
ATE-mix, oral, Rat: 2000 - 5000 mg/kg.

Range [%]	Substance
10 - <20	Ethylene dimethacrylate, CAS: 97-90-5 LD50, oral, Rat: 3300 mg/kg (RTECS).
1 - <10	Methacrylic acid, monoester with Propan-1,2-diole, CAS: 27813-02-1 LD50, dermal, Rabbit: > 5000 mg/kg (IUCLID). LD50, oral, Rat: > 4000 mg/kg (IUCLID).
0,1 - <1	1,1'-(p-Tolylimino)dipropan-2-ol, CAS: 38668-48-3 LD50, oral, Rat: 27,5 mg/kg.

Serious eye damage/irritation not determined

Skin corrosion/irritation not determined

Respiratory or skin sensitisation Sensitizing.

Specific target organ toxicity — single exposure not determined

Specific target organ toxicity — repeated exposure not determined

Mutagenicity There is no evidence of any mutagenic effects.

Reproduction toxicity There is no evidence of any reproductive toxicity effects.

Carcinogenicity There is no evidence of any carcinogenic effects.

General remarks

The product was classified on the basis of the calculation procedure of the preparation directive.

Toxicological data of complete product are not available.

SECTION 12: Ecological information

12.1 Toxicity

Range [%]	Substance
10 - <20	Ethylene dimethacrylate, CAS: 97-90-5
	LC50, (96h), Danio rerio: 15,95 mg/l (OECD 203).
	EC50, (3h), Pseudomonas putida: 570 mg/l (OECD 209).
1 - <10	Methacrylic acid, monoester with Propan-1,2-diole, CAS: 27813-02-1
	LC50, (48h), Leuciscus idus: 493 mg/L (IUCLID).
	EC10, (16h), Pseudomonas putida: 1140 mg/l (IUCLID).
0,1 - <1	1,1'-(p-Tolylimino)dipropan-2-ol, CAS: 38668-48-3
	LC50, (96h), fish: 17 mg/l.
	EC50, (48h), Daphnia magna: 28,8 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

No classification on the basis of the calculation procedure of the preparation directive.
Ecological data of complete product are not available.
The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the disposal contractor/authorities if necessary.

Waste no. (recommended)

080409*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110*
150102

SECTION 14: Transport information

14.1 UN number

See SECTION 14.2 in accordance with UN shipping name

MKT Metall-Kunststoff-Technik GmbH & Co. KG
67685 Weilerbach

Date printed 09.02.2015, Revision 25.03.2014

Version 03. Supersedes version: 02

Page 7 / 9

14.2 UN proper shipping name

Transport by land according to ADR/RID	NO DANGEROUS GOODS
Inland navigation (ADN)	NO DANGEROUS GOODS
Marine transport in accordance with IMDG	NOT CLASSIFIED AS "DANGEROUS GOODS"
Air transport in accordance with IATA	NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name

14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (Reach); 1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC
TRANSPORT-REGULATIONS	DOT-Classification, ADR (2013); IMDG-Code (2013, 36. Amdt.); IATA-DGR (2013).
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011). CHIP 3/ CHIP 4
- Observe employment restrictions for people	Observe employment restrictions for young people.
- VOC (1999/13/CE)	0 %

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 R-phrases (SECTION 3)

R 37: Irritating to respiratory system.
R 43: May cause sensitisation by skin contact.
R 36: Irritating to eyes.
R 25: Toxic if swallowed.
R 41: Risk of serious damage to eyes.
R 52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 48/20: Harmful - danger of serious damage to health by prolonged exposure through inhalation.

16.2 Hazard statements (SECTION 3)

H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
H318 Causes serious eye damage.
H301 Toxic if swallowed.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

16.3 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified Chemical Substances
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
TLV@/TWA = Threshold limit value – time-weighted average
TLV@STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.4 Other information

Classification procedure

STOT SE 3: H335 May cause respiratory irritation. (Calculation method)
Skin Sens. 1: H317 May cause an allergic skin reaction. (Calculation method)

Modified position

SECTION 3 been added: Quartz (< 10µm)
SECTION 2 been added: The product is classified and required to be labelled in accordance with EC-Directives
SECTION 3 been added: The quartz in this preparation is not available on foreseeable use.
SECTION 4 been added: Take off contaminated clothing and wash before reuse.
SECTION 4 deleted: Change soaked clothing immediately.
SECTION 5 deleted: Risk of formation of toxic pyrolysis products.
SECTION 5 been added: In the event of fire the following can be released:
SECTION 7 been added: Take off contaminated clothing and wash before reuse.
SECTION 8 been added: Protect the environment by applying appropriate control measures to prevent or limit emissions.
SECTION 8 deleted: See SECTION 6+7.
SECTION 16 deleted: Calculation method
SECTION 16 deleted: Observe employment restrictions for mothers-to-be and nursing mothers.
SECTION 16 been added: Calculation method
SECTION 16 been added: Calculation method



Copyright: Chemiebüro®

MKT Metall-Kunststoff-Technik GmbH & Co. KG
67685 Weilerbach

Date printed 09.02.2015, Revision 25.03.2014

Version 03. Supersedes version: 02

Page 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

MKT Injektionsmörtel VMU-PLUS, Comp. B

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Adhesive mortar for fastening elements" B-Component (Hardener)

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

MKT Metall-Kunststoff-Technik GmbH & Co. KG
Auf dem Immel 2
67685 Weilerbach / GERMANY
Phone +49(0)6374-91 16-0
Fax +49(0)6374-91 16-60
Homepage www.mkt.de
E-mail info@mkt.de

Address enquiries to

Technical information

mkt@mkt.de

Safety Data Sheet

mkt@mkt.de

1.4 Emergency telephone number

Advisory body

+49 (0)89-19240 (24h) (english)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008 [CLP]

Skin Sens. 1: H317 May cause an allergic skin reaction.
Eye Irrit. 2: H319 Causes serious eye irritation.

2.1.2 Classification according to Directive 67/548/EEC or 1999/45/EC

Sensitizing. - R 43: May cause sensitisation by skin contact.

2.2 Label elements

The product is required to be labelled in accordance with GHS/CLP-Directives.

Labelling according to Regulation (EC) 1272/2008

Hazard pictograms



Signal word

WARNING

Contains:

Dibenzoyl peroxide

Hazard statements

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P261 Avoid breathing vapours.
P280 Wear protective gloves/eye protection/face protection.
P363 Wash contaminated clothing before reuse.
P501 Dispose of contents/container to in accordance with local/regional/national/international regulation.

2.3 Other hazards

Environmental hazards

Does not contain any PBT or vPvB substances.

Other hazards

Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
10 - <20	Dibenzoyl peroxide
	CAS: 94-36-0, EINECS/ELINCS: 202-327-6, EU-INDEX: 617-008-00-0
	GHS/CLP: Org. Perox. B: H241 - Eye Irrit. 2: H319 - Skin Sens. 1: H317
	EEC: E-Xi, R 3-7-36-43
1 - <5	Reaction mass of Diethylene glycole dibenzoate, Dipropylene glycole dibenzoate and Triethylene glycol dibenzoate
	ECB-Nr.: 01-2119535193-44-XXXX
	EEC: R 52/53
< 5	2-Ethylhexyl benzoate
	CAS: 5444-75-7, EINECS/ELINCS: 226-641-8
	GHS/CLP: Aquatic Chronic 4: H413
	EEC: R 53
1 - <5	Quartz (< 10µm)
	CAS: 14808-60-7, EINECS/ELINCS: 238-878-4
	GHS/CLP: STOT RE 1: H372
	EEC: Xn, R 48/20

Comment on component parts

The quartz in this preparation is not available on foreseeable use.
Substances of Very High Concern - SVHC: substances are not contained or are below 0,1%.
For full text of H-statements and R-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Take off contaminated clothing and wash before reuse.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek for medical treatment.

Skin contact

In case of contact with skin wash off immediately with soap and water.
Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion

Supply with medical care.
Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions
Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide.
Dry powder.
Water spray jet.

Extinguishing media that must not be used

Full water jet
Foam.

5.2 Special hazards arising from the substance or mixture

In the event of fire the following can be released:
Carbon monoxide (CO)

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.
Fire residues must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Use personal protective equipment.
High risk of slipping due to leakage/spillage of product.
Keep away from all sources of ignition.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up mechanically.
Take up residues with absorbent material (e.g. sand, sawdust, generalpurpose binder, diatomaceous earth).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.
Keep away from all sources of ignition - Refrain from smoking.
Take off contaminated clothing and wash before reuse.
Do not eat, drink, smoke or take drugs at work.
Wash hands before breaks and after work.
Use barrier skin cream.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Prevent penetration into the ground.
Do not store together with food and animal food/diet.
Keep container in a well-ventilated place.
Keep container tightly closed.
Keep in a cool place. Store in a dry place.
Store in a dark place.
Protect from atmospheric moisture and water.
Recommended storage temperature: 5 - 25 °C

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Range [%]	Substance
10 - <20	Dibenzoyl peroxide
	CAS: 94-36-0, EINECS/ELINCS: 202-327-6, EU-INDEX: 617-008-00-0
	Long-term exposure: 5 mg/m ³
1 - <5	Quartz (< 10µm)
	CAS: 14808-60-7, EINECS/ELINCS: 238-878-4
	Long-term exposure: 0,15 mg/m ³ , HSE, NIOSH, OSHA
1 - <20	Glycerol
	CAS: 56-81-5, EINECS/ELINCS: 200-289-5
	Long-term exposure: 10 mg/m ³ , (mist)

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation.
Eye protection	Tightly fitting goggles.
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. In splash contact Nitrile rubber, >120 min (EN 374). In full contact: Butyl rubber, >480 min (EN 374).
Skin protection	Protective clothing.
Other	Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of these equipments to chemicals should be ascertained with the respective supplier.
Respiratory protection	If ventilation insufficient, wear respiratory protection. Short term: filter apparatus, combination filter A-P2.
Thermal hazards	not applicable
Delimitation and monitoring of the environmental exposition	Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	pasty
Color	black
Odor	characteristic
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	not determined
Flash point [°C]	116
Flammability (solid, gas) [°C]	not determined
Lower explosion limit	not determined
Upper explosion limit	not determined
Oxidizing properties	not determined
Vapour pressure/gas pressure [kPa]	not determined
Density [g/ml]	not determined
Bulk density [kg/m ³]	not applicable
Solubility in water	insoluble
Partition coefficient [n-octanol/water]	not determined
Viscosity	not determined
Relative vapour density determined in air	not determined
Evaporation speed	not determined
Melting point [°C]	not determined
Autoignition temperature [°C]	not determined
Decomposition temperature [°C]	not determined

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4 Conditions to avoid

Strong heating.
See SECTION 7.2.

10.5 Incompatible materials

Strong oxidizing agent.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Range [%]	Substance
< 5	2-Ethylhexyl benzoate, CAS: 5444-75-7
	LD50, dermal, Rabbit: >5000 mg/kg bw.
	LD50, oral, Rat: >2000 mg/kg bw.
10 - <20	Dibenzoyl peroxide, CAS: 94-36-0
	LD50, oral, Rat: 7710 mg/kg (HSDB).
	LC50, inhalative, Rat: > 24,3 mg/l 4 h.

Serious eye damage/irritation	Slight irritant effect - does not require labelling.
Skin corrosion/irritation	not determined
Respiratory or skin sensitisation	Sensitizing.
Specific target organ toxicity — single exposure	not determined
Specific target organ toxicity — repeated exposure	not determined
Mutagenicity	There is no evidence of any mutagenic effects.
Reproduction toxicity	There is no evidence of any reproductive toxicity effects.
Carcinogenicity	There is no evidence of any carcinogenic effects.
General remarks	

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 12: Ecological information

12.1 Toxicity

Range [%]	Substance
10 - <20	Dibenzoyl peroxide, CAS: 94-36-0
	LC50, (96h), fish: 2 mg/l.
	EC50, (48h), Daphnia magna: 2,91 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Ecological data of complete product are not available.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the disposal contractor/authorities if necessary.

Waste no. (recommended)

080409*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110*
150102

SECTION 14: Transport information

14.1 UN number

See SECTION 14.2 in accordance with UN shipping name

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

See SECTION 14.2 in accordance with UN shipping name

14.4 Packing group

See SECTION 14.2 in accordance with UN shipping name

14.5 Environmental hazards

See SECTION 14.2 in accordance with UN shipping name

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42; 648/2004; 1907/2006 (Reach); 1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC
TRANSPORT-REGULATIONS	DOT-Classification, ADR (2013); IMDG-Code (2013, 36. Amdt.); IATA-DGR (2013).
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011). CHIP 3/ CHIP 4
- Observe employment restrictions for people	Observe employment restrictions for young people.
- VOC (1999/13/CE)	0 %

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 R-phrases (SECTION 3)

R 3: Extreme risk of explosion by shock, friction, fire or other sources of ignition.
R 7: May cause fire.
R 36: Irritating to eyes.
R 43: May cause sensitisation by skin contact.
R 53: May cause long-term adverse effects in the aquatic environment.
R 48/20: Harmful - danger of serious damage to health by prolonged exposure through inhalation.
R 52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16.2 Hazard statements (SECTION 3)

H372 Causes damage to organs through prolonged or repeated exposure.
H413 May cause long lasting harmful effects to aquatic life.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H241 Heating may cause a fire or explosion.

16.3 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified Chemical Substances
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
TLV@TWA = Threshold limit value – time-weighted average
TLV@STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.4 Other information

Classification procedure

Skin Sens. 1: H317 May cause an allergic skin reaction. (Calculation method)
Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)

Modified position

SECTION 3 been added: Reaction mass of Diethylene glycole dibenzoate, Dipropylene glycole dibenzoate and Triethylene glycol dibenzoate
SECTION 3 been added: Quartz (< 10µm)
SECTION 3 been added: The quartz in this preparation is not available on foreseeable use.
SECTION 4 been added: Take off contaminated clothing and wash before reuse.
SECTION 4 deleted: Change soaked clothing immediately.
SECTION 5 deleted: Risk of formation of toxic pyrolysis products.
SECTION 5 been added: In the event of fire the following can be released:
SECTION 7 been added: Take off contaminated clothing and wash before reuse.
SECTION 7 been added: Prevent penetration into the ground.
SECTION 8 been added: Protect the environment by applying appropriate control measures to prevent or limit emissions.
SECTION 8 deleted: See SECTION 6+7.
SECTION 12 been added: Ecological data of complete product are not available.
SECTION 16 deleted: Observe employment restrictions for mothers-to-be and nursing mothers.
SECTION 16 been added: Calculation method
SECTION 16 been added: Calculation method

Copyright: Chemiebüro®