
1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name EPCON™ G5 PRO
Synonyms EG5P600 - PART NUMBER

1.2 Uses and uses advised against

Uses EPOXY ADHESIVE
Two component epoxy based adhesive in a combined cartridge that will deliver 2 parts resin to 1 part hardener for mixing and application.

1.3 Details of the supplier of the product

Supplier name RAMSETREID AU (A DIVISION OF ITW AUSTRALIA PTY LTD)
Address 1 Ramset Drive, Chirnside Park, VIC, 3116, AUSTRALIA
Telephone 1300 780 063
Fax 1300 780 122
Email enquiry@ramset.com.au
Website <http://www.ramset.com.au>

1.4 Emergency telephone numbers

Emergency +65 6746 1177 (Mon-Fri 8:30-17:30)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Corrosive to Metals: Category 1

Health Hazards

Acute Toxicity: Oral: Category 4
Skin Corrosion/Irritation: Category 1B
Skin Sensitisation: Category 1
Serious Eye Damage / Eye Irritation: Category 1

Environmental Hazards

Aquatic Toxicity (Chronic): Category 2

2.2 GHS Label elements

Signal word DANGER

Pictograms



PRODUCT NAME EPCON™ G5 PRO**Hazard statements**

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

Prevention statements

P234	Keep only in original packaging.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response statements

P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P321	Specific treatment is advised - see first aid instructions.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P391	Collect spillage.

Storage statements

P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner liner.

Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS**3.1 Substances / Mixtures**

Ingredient	CAS Number	EC Number	Content
BISPHENOL-A-(EPICHLORHYDRIN), REACTION PRODUCT	25068-38-6	500-033-5	<50%
1,3-CYCLOHEXANEDIMETHANAMINE	2579-20-6	219-941-5	<20%
FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL	9003-36-5	500-006-8	<20%
REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-CHLOROMETHYLOXIRANE(1:2)	933999-84-9	618-939-5	<10%
PHENOL, STYRENATED	61788-44-1	262-975-0	<5%
M-PHENYLENEBIS(METHYLAMINE)	1477-55-0	216-032-5	<2%
SALICYLIC ACID	69-72-7	200-712-3	<2%
ADDITIVE(S)	-	-	Remainder

4. FIRST AID MEASURES**4.1 Description of first aid measures**

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

PRODUCT NAME EPCON™ G5 PRO

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion

For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

First aid facilities

Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide, foam or water fog. Prevent contamination of drains or waterways.

5.2 Special hazards arising from the substance or mixture

Combustible. May evolve toxic gases (carbon/ nitrogen oxides and hydrocarbons) when heated to decomposition.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

- 2X
- 2 Fine Water Spray.
- X Wear liquid-tight chemical protective clothing and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Formaldehyde	SWA [AUS]	1	1.2	2	2.5
m-Xylene-a,a'-diamine	SWA [AUS]	--	0.1 (Peak)	--	--

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Maintain vapour levels below the recommended exposure standard.

PPE

- Eye / Face** Wear splash-proof goggles.
- Hands** Wear viton® or nitrile gloves.
- Body** When using large quantities or where heavy contamination is likely, wear coveralls.
- Respiratory** Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. If cutting or sanding with potential for dust generation, wear a Class P1 (Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	RED PASTE (PART A); BEIGE PASTE (PART B)
Odour	CHARACTERISTIC ODOUR
Flammability	COMBUSTIBLE
Flash point	> 100°C
Boiling point	> 35°C (PART A)
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Relative density	1.4 to 1.5 (PART A); 1.7 to 1.8 (PART B)
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

May be corrosive to metals.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerisation is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid) and alkalis (e.g. sodium hydroxide).

10.6 Hazardous decomposition products

May evolve toxic gases (carbon/ nitrogen oxides and hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Harmful if swallowed. Ingestion may result in burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
BISPHENOL-A-(EPICHLORHYDRIN), REACTION PRODUCT	> 15 g/kg (rat)	> 23 g/kg (rabbit)	--
1,3-CYCLOHEXANEDIMETHANAMINE	> 300 - 2,000 mg/kg (rat)	--	--
FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL	> 2 g/kg (rat)	> 400 mg/kg (rat)	--
REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-CHLOROMETHYLOXIRANE(1:2)	1681 to 3928 mg/kg bw (rat) 6 hours	--	--
M-PHENYLENEBIS(METHYLAMINE)	930 mg/kg (rat)	2000 mg/kg (rabbit)	700 ppm/1 hour (rat)
SALICYLIC ACID	891 mg/kg (rat)	> 2000 mg/kg (rat)	> 900 mg/m ³ (rat)

Skin Causes burns. Contact may result in irritation, redness, pain, rash, dermatitis and possible burns.

Eye Causes burns. Contact may result in irritation, lacrimation, pain, redness and possible burns.

Sensitisation May cause an allergic skin reaction. This product is not classified as a respiratory sensitiser.

Mutagenicity Not classified as a mutagen.

Carcinogenicity Not classified as a carcinogen.

Reproductive Not classified as a reproductive toxin.

STOT - single exposure Over exposure may result in irritation of the nose and throat, coughing and ulceration.

STOT - repeated exposure Long term exposure to epoxy resins may be harmful to the blood and hematopoietic systems (NZ CCID).

Aspiration This product does not present an aspiration hazard.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal	Mix components together to neutralise, wearing appropriate protective equipment - do not seal container until reaction is complete. Dispose of the reaction product in accordance with advice from your State's Environmental Protection Authority.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	2735	2735	2735
14.2 Proper Shipping Name	AMINES, LIQUID, CORROSIVE, N.O.S. (contains 1,3-cyclohexanedimethanamine)	AMINES, LIQUID, CORROSIVE, N.O.S. (contains 1,3-cyclohexanedimethanamine)	AMINES, LIQUID, CORROSIVE, N.O.S. (contains 1,3-cyclohexanedimethanamine)
14.3 Transport hazard class	8	8	8
14.4 Packing Group	II	II	II

14.5 Environmental hazards

Marine Pollutant.

14.6 Special precautions for user

Hazchem code	2X
GTEPG	8A1
EmS	F-A, S-B

Other information The environmentally hazardous substance mark is not required when transported in packages of less than 5 kg/L (UN Model Regulations: Special Provision 375; IATA: Special Provision A197; IMDG: Special Provision 969) or less than 500 kg/L by Australian Road and Rail.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule	Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).
Inventory listings	AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) All components are listed on AIIC, or are exempt. NEW ZEALAND: NZIoC (New Zealand Inventory of Chemicals) All components are listed on the NZIoC inventory, or are exempt.

16. OTHER INFORMATION

Additional information	WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (e.g. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.
-------------------------------	---

EPOXY - PHENOXY RESINS AND POLYURETHANES: Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered non toxic.

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGE (TWA) or WES (WORKPLACE EXPOSURE STANDARD) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

PRODUCT NAME EPCON™ G5 PRO

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmtglobal.com

[End of SDS]