




RAMPLUG

Universal Nylon Lightweight Anchor



Performance		Material	Installation					



MATERIAL

Body:
Polyamid 6

Technical Data

TYPE	Ø Woodscrew	Ø Drill bit	Anchor length
	d	d _o	L
DNP05	2.5 - 4	5	25
DNP06	3.5 - 5	6	30
DNP08	4.5 - 6	8	40
DNP10	6 - 8	10	50
DNP12	8 - 10	12	60
DNP14	10 - 12	14	70
DNP10 PV	-	10	50

PV: version with threaded head M8x125

Recommended Load and Ultimate Loads

TYPE	Ø Woodscrew	Concrete C20/25		Clay brick		Hollow clay brick		Aerated con.	Concrete C20/25		Aerated con.
		N _{rec} *	N _{u,m} *	N _{rec} *	N _{u,m} *	N _{rec} *	N _{u,m} *		N _{u,m} *	V _{rec} *	
DNP05	4	0.3	1.5	0.3	1.5	0.20	1.0	0.22	0.3	3.1	0.16
DNP06	5	0.5	2.5	0.5	2.5	0.25	1.3	0.44	0.8	4.9	0.23
DNP08	6	0.8	4.0	0.8	4.0	0.35	1.8	0.65	1.0	5.8	0.42
DNP10	8	1.2	6.0	1.1	5.5	0.45	2.3	0.91	1.2	7.3	0.71
DNP12	10	1.8	9.0	1.5	7.5	0.55	2.8	1.33	2.8	22.3	0.96
DNP14	12	2.8	14.0	1.8	9.0	0.7	3.5	1.50	3.0	24.0	1.10

* Indicative values