TrakFast™ 800
Accessories & Consumables

Ramset™

Gas Technology Systems

Trades & Applications

	Ceiling and Partitioning Contractor	Door & Window Contractor	Wet Trade Contractor	Pest Control Contractor
Track to concrete	✓			
Track to steel	✓			
Plywood to steel			✓	
Sacrificial steel formwork to steel			✓	
Pest control mesh to concrete				✓
Wall-tie & bonding bar		✓	✓	

TrakFast™800

Part No	Description	Order Qty
9A-TRAK-FAST	TrakFast™ Pulsa™ Gas Tool + 2 x Lithium-Ion Batteries	1

Kit includes: TrakFast™800 Tool, 20-pin magazine, high impact carry case, 2 batteries, battery charger, safety glasses and instruction manual.

Accessories

Part No	Description	Order Qty.
9A-TRAK-20MG *	Pulsa 800 20 Pin Magazine (a)	1
9A-TRAK-50MG *	Pulsa 800 50 Pin Magazine (b)	1
9A-TRAK-BATT	Pulsa 800 Lithium-ion Battery (c)	1
9A-TRAK-CHAR	Pulsa 800 Lithium-ion Battery Charger (d)	1
9A-TRAK-MAGH *	Pulsa 800 Magnetic Washer Adaptor (e)	1
9A-TRAK-FUEL *	Pulsa 800 Fuel Cell (f)	1
9A-TRAK-TFFG *	TrakFast™800 Fastener Guide	1
9A-TRAK-DLUB *	Gas Tool Degreaser and Lubricant	1
9A-TRAK-CMFG *	CableMasterTM800 Fastener Guide	1

Heavy Duty Pin Range for Steel and Hard Concrete Fixing

The Ramset™ range of Premium Drive Pins has been designed for steel and hard concrete applications.

Specifications

Raw Material	Carbon Steel
Corrosion Protection	Zinc Mechanically Plated (Min. coating 10µm)
Nominal Head Diameter	6.4mm
Nominal Shank Diameter	3.0 / 2.7mm
Shear Strength	1200N/mm^2
Tensile Strength	1950N/mm^2
Hardness	53-56HR$_C$

Part No	Description	Length	Order Qty
9A-TRAK-HC15 *	Premium Steel Pin	15mm	500
9A-TRAK-HC17 *	Premium Hard Concrete/Steel	17mm	500
9A-TRAK-HC22	Premium Hard Concrete/Steel	22mm	500

10 strip collation (suitable for use in 20 and 50-pin magazines)

*** Non stocking item**

Stainless Steel Pin for Special Applications

The Ramset™ SS6 Stainless Steel Pins has been designed for special applications such as fixing wall tie and bonding bar systems to precast and reinforced concrete columns or walls.

Specifications

Raw Material	Stainless Steel Grade 304
Nominal Head Diameter	6.4mm
Nominal Shank Diameter	2.6mm
Pull-out Strength	Exceeds 1kN (in concrete)

Part No	Description	Length	Order Qty
9A-TRAK-SS619	Stainless Steel Pins SS6-19	19mm	500

10 strip collation (suitable for use in 20 and 50-pin magazines)

Recommended Loading

HC6 Pins		Characteristic Resistance		Recommended Load*	
		Tension N_{rk} (kN)	Shear N_{rk} (kN)	Tension N_{rk} (kN)	Shear N_{rk} (kN)
C20/25 to C60/70	H_{nom} = 10mm	0.34	0.75	0.10	0.25
	H_{nom} = 15mm	0.87		0.30	
	H_{nom} = 18mm	1.19		0.40	
	H_{nom} = 20mm	1.41		0.47	
Steel = 410-450 N/mm^2 Steel = 500-550 N/mm^2	H_{nom} = 6.5mm	5.0	3.6	1.5	1.2

* The above information is for reference only. On-site testing is recommended.

TAPCON
CONSTRUCTION - TRADING

Office address:

TRUONG AN PHU CONSTRUCTION TRADING CO., LTD.
24A Bui Dinh Tuy Str., Ward 26, Binh Thanh Dist., Ho Chi Minh City, Vitenam
Tel.: (+84) 28-3511.8693 | Email: tapcon@tapcon.com.vn